



TECHNICAL DATA SHEET (TDS)

Woven Roving

N° SF2014-19
 Date of previous issue:
 Date of issue: 03/02/2016
 Version: 1

Product/Prodotto/Produit:

WOVEN ROVING /STUOIA /TISSU ROVING

Reference:

SF500

Weight / Gramatura / Masse surfacique (g/m²)

500 +/- 5%

PRODUCT DESCRIPTION

Weave/Armatura/Armure

PLAIN / TELA / TAFFETAS

Warp/Ordito/Chaine

2,2 x Roving 1200 Tex

Weft/Trama/Trame

2,0 x Roving 1200 Tex

Edges/Giro/Bordure

Hot melt / glass yarn 68/136 tex

Weight / Gramatura / Masse surfacique (+/-5%)

500g / m²

INPUT ROVING SPECIFICATION

Filament diameter	μ	17
Weight	Tex	1200 +/-10%
LOI	%	1.0
Moisture/Umidita/Humidité max	%	0,15 max

PACKING

Individual PE bag - sacco di PE per ogni rotolo - sac PE pour chaque rouleau

Inner core/Anima/Tube interne (diameter)		3'
Standard width/ Altezza/Largeur (-0/+2cm)*	cm	125
Standard Length/Lunghezza/longueur (+/-5%) ML	ML	60
Net weight per roll /Peso netto /Poids net (+/-5%)	Kg	37,5
Net weight per pallet /Peso netto /Poids net (+/-5%)	Kg	1125



Via Rasica, 56 – 24040 Osio Sopra (Bg)
 Tel. 035.504236 – Fax 035.506993
 P.IVA / C.F.: 03866860160