

## **Chopped Strand**

Product	Product Characteristic	Resin System	Example of End-Product Application	
473 / 473P / 473H / 473HP	Compatible with most nylon		Plastic chairs, Motorcycle cases, Roller skate wheels	
173H		PA6 / PA66 / PA46  rolysis resistance  Radiator grilles, Thermal insu		
174	Hydrolysis resistance		Radiator grilles, Thermal insulation	
492	Used with nylon & PET	PA / PET	Containers, Electrical components	
183E 183F	Most suitable for PBT resin system	PBT / PET / ABS	Electrical switches, Computer fans, PET bottles, Connectors, Headlight cases	
202P 203P	Coupled & uncoupled PP	PP	Bumpers, Pump cases, Headlight cases	
301P	POM application	РОМ	Gears, Electrical components, Office equipment	
473A	Designed for Polycarbonate resin	PC	Cell phones, TFT-LCD's and Digital Video cases	
422	11	LCP / PPS / PS / PVC	Cell phone cases, Motherboard connectors, Drinking water applications	
475	High temp. resin system	PPS / PPO / PVC	Cell phone cases, Motherboard connectors	
47.7		LCP	Connectors, Electrical applications	
101C	Designed for a wide variety of BMC	UP / Phenolic / Epoxy	Building construction materials, Transformers, Decorations	
405D	Phenolic friction application	UP / Phenolic	Break pads, Decorations	

## **Chopped Strand Food & Water Contact Approval**

Resin	Product	FDA	EU 10/2011	BfR LII
	174	0	0	0
D.A.	473H	0	0 .	0
PA	173H	0	0	0
	173X	0	0	0
PP	202P	0	0	0
PP	203P	0	0	0
ABS	183F	0	0	0
LCP / PPS PVC / PS	422	0	0	. 0

